



In 2011, the first panel radiator in Iran, the result of joint cooperation between Iran and Turkey to transfer world-class knowledge in the form of AYIS Company, which was established in 2010.

Utilization of advanced production lines and distinctive quality of this product caused a wide acceptance in the market, so that in a short period of time, the capacity of production lines tripled

Azar Garmaye Sahand Tabriz(AGST) Company, one of the subsidiaries of Butan Industrial Group in 2019, purchased panel radiator lines production from AYIS Company to enable the development of the market more than before.

As the largest and most advanced manufacturer of panel radiators in Iran, we are committed to providing durable and quality products and we appreciate your trust.

Features and Specifications

- Modern and elegant design
- Compatibility With Wall Hung Gas Boiler
- Need less ventilation
- Double Panels & Double Convectors
- Standard Axis 500
- Special Phosphate covering
- Electrostatic Powder (RAL 9016) white Color covering
- High thermal efficiency due to welding of convectors directly on radiator water ducts
- Use of steel sheets to the thickness of 1.12 mm
- Easy cleaning due to easiness of picking up the grid and covers of radiator
- Production conforming to EN442 Standard
- High efficiency, Energy Grade C
- Installation from left and right side



| length | Thermal Capacity | Dewatering Volume | Weight | Width | Height | AXIS | Lab. pressure (min,max) | Max. operating temperature |
|--------|-------------------------|----------------------|--------|-------|--------|------|----------------------------|----------------------------|
| (mm) | Δt = 60 c° (Kcal/hr) | (lit) | (Kg) | (mm) | (mm) | (mm) | (Bar) | (c°) |
| 600 | 1104 | 3.35 | 15.24 | 104 | 555 | 500 | 7-10 | 110 |
| 800 | 1473 | 4.46 | 20.32 | 104 | 555 | 500 | 7-10 | 110 |
| 1000 | 1842 | 5.58 | 25.40 | 104 | 555 | 500 | 7-10 | 110 |
| 1200 | 2209 | 6.69 | 30.48 | 104 | 555 | 500 | 7-10 | 110 |
| 1400 | 2577 | 7.81 | 35.56 | 104 | 555 | 500 | 7-10 | 110 |
| 1600 | 2945 | 8.92 | 40.64 | 104 | 555 | 500 | 7-10 | 110 |
| 1800 | 3313 | 10.04 | 45.72 | 104 | 555 | 500 | 7-10 | 110 |
| 2000 | 3681 | 11.15 | 50.80 | 104 | 555 | 500 | 7-10 | 110 |









